

HG "floor glue remover, extra strong"

EXTRA STRONG AND SUPER FAST WORKING GLUE REMOVER, SUITABLE FOR REMOVING. THE MOST STUBBORN GLUE REMAINS SUCH AS: BOTH SOLVENT AND WATER BASED GLUES GLUES FOR CARPETS, LINOLEUM, VINYL AND PVC GLUES FOR WOODEN OR CORK FLOORS, FLOOR TILES AND OTHER WALL AND FLOOR COVERINGS. FIX AND MOUNTING GLUE.

- APPLICATION

For carpets, linoleum, PVC, vinyl, wooden or cork floors, floor tiles, and other wall and floor coverings.

- DIRECTIONS FOR USE

First test HG "floor glue remover" on a small and inconspicuous area of the surface. Cut carpet etc. into strips and roll up. (Vinyl) floor covering that does not come loose should first be perforated using a pricking roller or a similar tool. The floor glue remover must be able to penetrate very well into glue layer in order to remove it. Remaining glue should be well covered with HG "floor glue remover" using a brush, for example. After 10-15 minutes scrape off the glue using a filling knife. Repeat the treatment, if necessary, allowing more time to work. Finally, rinse the surface with water and allow it to dry before applying a new wall or floor covering.

- ATTENTION

During use keep the area well ventilated. Keep in a cool and dry spot. This product is not so effective on acrylic-based glues. Do not allow the HG "floor glue remover" to dry during application or else the glue will reattach itself to the surface.

- PRODUCT INFORMATION

Characteristics	: highly concentrated acid cleaner.
S.G.	: ± 1,0 g/ml
Usage	: 0.5 – 1.00 L/m ²
Components	: methylal, 1,3-dioxolane, anionics, cellulose, esters

- PACKAGING : 6 x 0.75 L

- PRECAUTIONS

R11- Highly flammable . **S2**- Keep out of the reach of children. **S16**- Keep away from sources of ignition- No smoking. **S24**- Avoid contact with skin. **S29**- Do not empty into drains. **S37**- Wear suitable gloves. **S46**- If swallowed, seek medical advice immediately and show this container or label .