

## Lithofin MN Colour Intensifier

### Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). This ready-to-use siloxane impregnator is solvent based and contains special colour intensifying components.

#### Technical Data:

Density: approx. 0,85 g/cm<sup>3</sup>

Appearance: liquid, colourless, clear

Odour: aromatic

pH-Value: n.a.

Flash Point: >25°C

Solubility in Water: not soluble

### Properties

Lithofin MN Colour Intensifier penetrates into the surface rendering it water repellent while at the same time intensifying the colour without producing any gloss. Surfaces appear more colourfull and fresh – wet effect. The water resistance reduces the sensitivity of the surface, largely preventing staining and facilitating maintenance. Lithofin MN Colour Intensifier does not form any layers, thereby maintaining the surfaces water permeability. The slip resistance of the surface is hardly affected. Durability: indoors and with correct maintenance nearly unlimited. Outdoors, depending on the type of stone, the colour will remain for approx. 1 to 2 years, the protective effect for approx. 5 to 7 years. Can be reapplied when the effect fades.

### Field of Use

For adding lustre to wall and floor surfaces, stairs, entrance areas, terraces, etc. which appear bland and colourless. Suitable for indoor and outdoor use.

Surfaces: all absorbent, porous natural stones (e.g. granite, gneiss, porphy, marble, limestone, slate, etc.) and engineered stones with rough, sawn, honed and flamed surfaces.

Please Note: for protecting polished and very finely honed natural and artificial stones, we recommend Lithofin STAINSTOP >W<, Lithofin MN Stain-Stop or Lithofin SPLAS-STOP.

### Directions for Use

The surface to be treated must be completely dry and clean. Where no prior experience exists or in cases of doubt, try the product in an inconspicuous area prior to use. Evenly apply a consistent amount of Lithofin MN Colour Intensifier with a brush, a roller or a cloth. On highly absorbent surfaces, this procedure may have to be repeated after five minutes. Do not allow the surface residues to dry. Residues must be completely removed within ten minutes with a cloth. On large surfaces, remove the residues with a squeegee and polish with a white pad.

Attention! treat only completely dry surfaces (drying time for newly laid surfaces up to 8 weeks, otherwise several days). Non-absorbent surfaces such as polished or fired materials such as porcelain or ceramic tiles can not be treated. Glass, wood, plastics and other surfaces sensitive to solvents must be protected against splashes.

Application Temperature: the temperature of the surface should be between 5°C and 25°C. Switch off under floor heating.

Drying Time: safe to walk on after approx. 30 minutes, completely dry after 24 hours.

Coverage: approx. 10m<sup>2</sup> per litre depending on the surface.

### Storage

Keep closed, cool and dry. Shelf life of up to four years. Open containers should be used quickly.

### Environmental Protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate. Clean containers can be recycled through collection systems.

### Safety

Contents: hydrocarbons; siloxane polymers; auxilliary agents.

Risk and Safety Phrases: flammable. Harmful by inhalation and in contact with skin. Irritating to respiratory system. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children. Do not breathe vapour. Avoid contact with skin. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

First Aid Procedures: remove contaminated soaked clothing immediately. In case of inhalation, ensure of fresh air. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

Emergency Procedures: in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

Additional Information is listed on the Material Safety Data Sheet.

#### ADR2003:

flammable liquid, n.o.s.

UN 1993, Class 3

Packaging Group III

### Packaging

1 litre bottle with child-proof cap (10 per box)

5 litre canister (2 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (GB11.04gps/3.03)

### Agents for Great Britain:

CASDRON Enterprises Ltd. • Alresford, Hanpshire SO24 9QF • Phone: (01962) 73 21 26 • Fax (01962) 73 53 73

Manufactured in Germany by: LITHOFIN AG • 73240 Wendlingen • e-mail: info@lithofin.de

[www.lithofin.com](http://www.lithofin.com)