

MATERIAL SAFETY DATA SHEET

NORCROS CEMENT-BASED ADHESIVES & LEVELLING COMPOUND

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER: Norcross Universal Levelling Compound; Norcross Pro 50 Levelling Compound; Norcross 2-Part Levelling Compound Powder; Norcross Rapid Repair Mortar; Norcross Wall & Floor Tile Adhesive White & Grey; Norcross One Part Flexible White & Grey; Norcross Fast Set Rock-Tite; Norcross Rapid Porcelain Grey; Norcross Rapid Porcelain & Stone White; Norcross Thick Bed Stone & Porcelain Grey & White; Norcross Rapid Porcelain Grey S1 Tile Adhesive; Norcross Rapid Porcelain White S1 Tile Adhesive; Norcross Standard Set Flexible White S1 Tile Adhesive; Norcross One Part Tile Direct to Wood; Norcross Tile Direct to Wood Rapid; Norcross One Part Sealing Slurry

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

Intended use: PC1 Cement-based adhesives for ceramic wall and floor tiling
PC1 Cement-based levelling compound for floors
PC1 Cement-based waterproofing membrane

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

NORCROS ADHESIVES
Harewood Street
Tunstall
Stoke on Trent
Staffordshire
ST6 5JZ
Tel: 01782 524 140
Fax: 01782 524141
E-mail: technical@norcross-adhesives.com

1.4 EMERGENCY TELEPHONE NUMBER: 44 (0) 1782 524 140

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

CLASSIFICATION UNDER CHIP

Xi Irritant
R36/38 Irritating to eyes and skin
R41 Risk of serious damage to eyes
Contains Chromium VI – may produce an allergic reaction

CLASSIFICATION UNDER CLP

Skin corrosion/irritation, Category 2, H315
Serious eye damage/Eye irritation, Category 1, H318
May cause respiratory irritation, Category 3, H335

2.2 LABEL ELEMENTS:

LABEL ELEMENTS UNDER CHIP

HAZARD SYMBOLS: Harmful



RISK PHRASES:	<p>P14 R36/38 R41</p>	<p>Contains Chromium VI. May produce an allergic reaction Irritating to eyes and skin Risk of serious damage to eyes.</p>
SAFETY PHRASES:	<p>S-2 S-25 S-26 S-28 S-36/37/39 S-46 S-56</p>	<p>Keep out of reach of children Avoid contact with eyes In case of contact with eyes rinse immediately with plenty of water and seek medical advice After contact with skin, wash immediately with plenty of water Wear suitable protective clothing, gloves and eye/face protection If swallowed seek medical advice immediately and show the container or label Dispose of this material and its container to hazardous or special waste collection point</p>

LABEL ELEMENTS UNDER CLP

HAZARD STATEMENTS:	H302	Harmful if swallowed
	H315	Causes skin irritation
	H318	Causes serious eye damage/Eye irritation
	H335	May cause respiratory irritation

SIGNAL WORDS: Danger

HAZARD PICTOGRAMS



PRECAUTIONARY STATEMENTS

PREVENTION:	P102	Keep out of reach of children
	P261	Avoid breathing dust
	P264	Wear protective gloves and eye protection
	P280	Wear protective gloves/protective clothing/eye protection/face protection
	P301 + P312	If swallowed: Call poison centre or doctor/physician if you feel unwell
	P310	Immediately call a poison centre or doctor/physician
	P332 + P313	If skin irritation occurs: Get medical advice/attention
	P305 + P351 + P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P501	Dispose of contents/container in accordance with local/regional regulations

2.3 OTHER HAZARDS

HUMAN HEALTH

When the cement-based powder is mixed with water, a strong alkaline paste is produced. When set, cement-based products may cause both irritant and allergic dermatitis. Irritant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individuals skin to hexavalent chromium salts.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 MIXTURES:

NAME	CAS -No	EINECS No	CHIP Classification	CLP Classification	Content
Calcium Hydroxide	1305-62-0	215-137-3	Xi; R36/38	Skin Corr./Irr. Cat 2:H315 Ser. Eye Dam./Eye Irr. Cat 1; H318 STOT – Single exposure: Respiratory tract irritation, Cat 3, H335	1 – 5%
Ordinary Portland Cement	65997-15-1		Xi; R41	Skin Corr./Irr. Cat 2:H315 Ser. Eye Dam./Eye Irr. Cat 1; H318	30 – 60%

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

AFTER INHALATION: Move affected personnel into fresh air
If nose or airways become inflamed seek medical attention.

AFTER INGESTION: Wash out mouth with clean water. Do not induce vomiting.
Drink plenty of water.
If symptoms develop or persist seek medical attention.

AFTER CONTACT WITH SKIN Remove contaminated clothing
Wash affected area thoroughly with soap and water.
If discomfort or irritation develops seek medical attention.

AFTER CONTACT WITH EYES: Make sure that any contact lenses are removed before rinsing opened eye using plenty of clean water for at least 15 minutes.
Seek medical attention if discomfort persists.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED
Irritant and allergic contact dermatitis

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED
Skin irritation. Seek medical advice if discomfort or irritation persist. Show this safety data sheet to the doctor in attendance.

SECTION 5: FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA
Product is non-flammable. Use extinguisher appropriate for the surrounding materials.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE
None

5.3 ADVICE FOR FIRE FIGHTERS
Product is non-flammable.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1 For non-emergency personnel

Wear suitable protective clothing – refer to section 8.
 Avoid contact with skin or inhalation of spillage, dust or vapour.

6.1.2 For emergency personnel

Wear suitable protective clothing – refer to section 8
 Avoid contact with skin or inhalation of spillage, dust or vapour.

6.2 ENVIRONMENTAL PRECAUTIONS

Avoid material entering drains or water courses or onto the ground.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Dampen spillage with water.
 Absorb in vermiculite, dry sand or earth and place into containers. Shovel into dry containers.
 Cover and move the containers. Flush the area with water.

6.4 REFERENCE TO OTHER SECTIONS

Sections 8 and 13 should be referred to.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Ensure good ventilation
 Avoid skin and eye contact
 Avoid the generation of airborne dust

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store in tightly closed original containers
 Store in dry, well ventilated areas at temperatures of 5 – 32°C
 Protect from frost and damp conditions

7.3 SPECIFIC END USE(S)

No special requirement.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

INGREDIENT NAME	CAS No	STD	LT EXP – 8 HRS
Calcium Hydroxide	1305-62-0	WEL	5mg/m ³
Ordinary Portland Cement	65997-415-1	WEL	10mg/m ³ total inhalable dust 4mg/m ³ respirable dust

(WEL = Workplace Exposure Limit)

8.2 EXPOSURE CONTROLS

ENGINEERING MEASURES:	Provide adequate ventilation including local extraction to ensure that the defined exposure limit is not exceeded. Provide eyewash station
RESPIRATORY EQUIPMENT:	If ventilation is insufficient, suitable respiratory protection must be provided
HAND PROTECTION:	Use suitable protective gloves.
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of skin contact.
HYGIENE MEASURES:	DO NOT SMOKE IN WORK AREA. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

(a) Appearance:	Grey cement-based powder
(b) Odour:	No odour
(c) Odour threshold:	Not determined
(d) pH:	Not applicable/Alkaline when wet
(e) Melting point/freezing point:	Not applicable
(f) Initial boiling point and boiling range:	Not applicable
(g) Flash point:	Not applicable
(h) Evaporation rate:	Not applicable
(i) Flammability (solid/ gas):	Not applicable
(j) Upper/lower flammability or explosive limits:	Not applicable
(k) Vapour pressure:	Not applicable
(l) Vapour density:	Not applicable
(m) Relative density:	~1.5 – 1.6
(n) Solubility(ies):	Not determined
(o) Partition co-efficient; n-octanol/water:	Not determined
(p) Auto-ignition temperature:	Not determined
(q) Decomposition temperature:	Not determined
(r) Viscosity:	Not applicable
(s) Explosive properties:	Not determined
(t) Oxidising properties:	Not determined

9.2 OTHER INFORMATION

Not applicable

SECTION 10: STABILITY AND REACTIVITY**10.1 REACTIVITY**

Stable when stored correctly

10.2 CHEMICAL STABILITY

Stable when stored correctly

10.3 POSSIBILITY OF HAZARDOUS REACTION

Stable

10.4 CONDITIONS TO AVOID

Protect from frost

Avoid contact with acids

Do not store in damp, wet or humid conditions

10.5 INCOMPATIBLE MATERIALS

Strong acids, strong oxidising agents

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Dioxide (CO₂) and Carbon Monoxide (CO) are created by high temperatures or fire.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

INHALATION:	May cause irritation to the respiratory system. May cause damage to mucous membranes in nose, throat, lungs and bronchial system. Harmful: Danger of serious damage to health by prolonged exposure through inhalation.
INGESTION:	May cause severe irritation of the mouth, oesophagus and the gastrointestinal tract.
SKIN CONTACT:	The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.
EYE CONTACT:	Risk of serious damage to eyes. May cause chemical eye burns.

11.1.2 SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

Repeated exposure in excess of the WEL has been linked with rhinitis and coughing. Skin exposure has been linked to allergic chromium dermatitis.

SECTION 12: ECOLOGICAL INFORMATION**12.1 TOXICITY**

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms

12.2 PERSISTENCE AND DEGRADABILITY

No data available

12.3 BIOACCUMULATIVE POTENTIAL

No data available

12.4 MOBILITY IN SOIL

The product is non-volatile.

The product is insoluble in water and will sediment in water systems. After hardening product is non-toxic

12.5 RESULTS OF PBT AND vPvB ASSESSMENT

No data available

12.6 OTHER ADVERSE EFFECTS

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

In accordance with local authority regulations

Contaminated Packaging: Empty bags or surplus product can be disposed of as building site or commercial waste.

13.1 WASTE TREATMENT METHODS**SECTION 14 TRANSPORT INFORMATION****14.3 TRANSPORT HAZARD CLASS(ES)**

ROAD TRANSPORT: Not classified as hazardous

RAIL TANSPORT: Not classified as hazardous

SEA TANSPORT: Not classified as hazardous

AIR TRANSPORT: Not classified as hazardous

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL73/78 AND THE IBC CODE

SECTION 15: REGULATORY INFORMATION**15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE**

SPECIFIC REGULATIONS: This product is classified as a mixture. CLP classification for information only.

15.2 CHEMICAL SAFETY ASSESSMENT

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: OTHER INFORMATION

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010

LEGAL DISCLAIMER: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.