

prime APD

Acrylic Primer for Walls and Floors

DESCRIPTION

Rapid-drying acrylic primer for tiling substrates.

Use for

- Preparing wall and floor backgrounds prior to fixing of ceramics, mosaics and natural stone tiles in dry or wet interior and exterior environments.
- May also be used with BAL ACRYBASE, BAL MULTIBASE, BAL ULTRABASE Levelling Compounds and with BAL WP1/Waterproofing Kit for Showers
- Use undiluted on
 - Plaster walls and plasterboard (when using a BAL cementitious adhesive)
 - Tongued and grooved floorboards
 - Anhydrite screed floors
- Use diluted 1:1 with clean water on:
 - Plaster walls (when using a BAL ready-mixed adhesive), only if dusty or porous
 - Cement floors

PRODUCT INFORMATION

Composition: Modified acrylic polymer dispersion.

Pack size: 2.5 litre

Key features: Stabilises dusty surfaces. Reduces porosity of backgrounds.

USAGE & SERVICE CONDITIONS

Walls	✓	Floors	✓
Worktops	✓	Interior	✓
Exterior	✓	Dry	✓
Wet	✓		

Showers (1)	✓
Heated Screeds	✓
Limited Movement/Vibration	✓

- (1) Do not use showers for at least 2 weeks after completion of grouting – BS 5385:Part 4:2009, clause 7.2.1.
 (2) Tiles must be grouted with a BAL Epoxy grout e.g. BAL-EASYPOXY.
 (3) Direct fixing in dry conditions only.
 (4) In wet conditions tank out with the BAL-WP1 TANKING SYSTEM.
 (5) Use undiluted.

BACKGROUNDS/BASES

Brick/Concrete	✓
Rendering	✓
Lightweight Blockwork (3)	✓
Plaster (4)	✓
Plasterboard	✓
Tile Backer Boards	✓
Floorboards (4)	✓
Anhydrite Screed (4) (5)	✓
Cement:Sand Screed	✓
Plywood Overlay (Floors) (4)	✓
Vinyl Tiles	✓

Usage: Coverage	
	Typical coverage [^] :
Undiluted	5 – 10m ² /litre
Diluted 1:1 with water	10 – 20m ² /litre

[^] Depends on porosity of substrate.

APPLICATION/USAGE

Usage procedure

IMPORTANT NOTE: Do NOT use in temperatures below 5°C.

1. Shake container well before use.
2. Ensure surfaces are free from dirt, grease and other loose materials. Brush down highly polished surfaces with a stiff bristled brush before priming.
3. Apply 2 coats of BAL PRIME APD using a clean brush from a container, diluted or undiluted as appropriate (see USAGE above). Allow to dry between coats.

NOTE: *If using on floor*, do NOT allow primer to form puddles.

4. Ensure even coverage.
5. Allow to dry thoroughly for 15-30 minutes before applying adhesive.
6. Clean product from tools and hands using clean water.

HEALTH & SAFETY INFORMATION/ GOOD PRACTICE ADVICE

For detailed information and safety guidance, please refer to Product Material Safety Data Sheet [MSDS].

TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on
Tel: 01782 591120 or 0845 600 1 222 or Fax: 01782 591121.

POWERSPEC

A unique computerised online specification system for the design and installation of ceramic, mosaic and natural stone tiling. Visit www.powerspeconline.com

SHELF LIFE

12 months under normal dry conditions. Protect from frost and direct sunlight. Store between 5°C and 30°C.

QUALITY AND ENVIRONMENTAL STANDARDS

Manufacturing quality assurance standards conform to BS EN ISO 9001. Satisfies the environmental management requirements and operational scope of ISO 14001.

25 YEAR GUARANTEE

All BAL products are supplied with a 25 year product guarantee to be free from manufacturing defects and to be fit for purpose. The guarantee covers materials replacement costs and labour.

This guarantee is subject to use of product in accordance with BAL's instructions and technical data, and good working practice. No liability can be accepted for any loss or damage arising from incorrect use of products or poor workmanship, over which BAL has no control.

Contact BAL Marketing Department for full details.

CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale.
Available on request.

For sales and technical queries, contact:

BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB, England
www.bal-adhesives.com

Sales

Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical

Tel: +44 (0) 1782 591120 or

+44 (0) 845 600 1 222

Fax: +44 (0) 1782 591121

Unit 622, Phase III

Northwest Business Park

Ballycoolin, Dublin 15, Ireland

Tel: +353 (0) 1 880 9210

Fax: +353 (0) 1 880 9211

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.

 Powerspec
www.powerspeconline.com



FM 01312



Prime APD